

## **Key Features**

- // Improved aesthetics with discreet perforations, a smoother finish and a class-leading, fully painted whiteness
- Enhanced acoustical absorption performance of 0.60  $\alpha_{w}$  for better acoustic comfort
- Fully painted, reinforced edges for a more robust tile and greater durability
- Mix and match modules for increased flexibility and a more complete project solution
- Easy to handle and re-engineered for a better,
- Ideal for every space



Edge Detail	Board	Tegular24	Tegular15			
	Q 	6.5 1 24				
Thickness (mm)	15	15	15			
Modules (mm)	600 x 600	600 x 600	600 x 600			
Suspension Systems	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS	Prelude 24 XL <sup>2</sup> / TLS Prelude 24 Sixty <sup>2</sup> XL <sup>2</sup> / TLS	Prelude 15 TL/ XL <sup>2</sup> Interlude HRC XL <sup>2</sup> Silhouette XL <sup>2</sup>			
Colour	Global White					
Sustainability			Securofins			
	44	A EN 13964 / E1	TAIED PROD			

**Acoustics** 





EN ISO 354 & EN ISO 11654 & EN ISO 717-1

<u>*</u> Z
EN ISO 10848-2

		Hz $\mathfrak{a}_{\scriptscriptstyle P}$								
	$a_{w}$	D <sub>nfw</sub>	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	0.60	34 dB	С	0.55	0.35	0.45	0.60	0.60	0.60	0.60

**Fire Reaction** 



Euroclass A2-s1, d0 EN 13501-1

**Performances** & Features



85%



95% RH











3.6 Kg/m<sup>2</sup>







If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on 0800 371 849 or email enquiries@zentia.com

TDS 133.1.05.23

